



Extrema

cat. B

63% polyurethane - 29% cotton - 8% polyester  
Flame retardant - 150.000 Martindale



450



3650



3750



150



250



350




1150




3250



750




1250



1350




2850



2750



4850



1050



950



850



4350



4050



3550



3150



550



650



2350



2950




2450



1650



3950



1550



1450



4650



3850




4550



4150




3350



4750




2550




1850



2650



1950



4250



1750




3050




3450



2050



4450



2150



2250

# Extrema

## Technical details

Composition	63% polyurethane - 29% cotton - 8% polyester
-------------	----------------------------------------------

Weight Gr./m<sup>2</sup> 480

Abrasion test Martindale - ISO 12947-2: 150.000 rubs

Lightfastness ISO 105-B02: 5/6

Solidity to sweat ISO 105-E04: 4/5

Flame retardant	BS 5852 crib 5 BS 5852-1 part I IMO resolution A.652 (16): 1989 EN 1021-2 UNI 9175 classe 1 IM TB 117 sez.E – p.1 (California)
-----------------	-----------------------------------------------------------------------------------------------------------------------------------------------

Treatment	ULTRA-FRESH: Anti-microbial agent
-----------	-----------------------------------

Features	Comfort and elasticity Waterproof Easy to clean Fire resistance Resistance to mould and bacteria Phthalates free
----------	---------------------------------------------------------------------------------------------------------------------------------

laCividdina

cat. B

2018